




MFA0300

Blower for Performance & High reliability

A standard AIRFAN blower's architecture with its **patented motor cooling system** and its unique **soundproofing housing**.

The **MFA0300** is perfectly suited for implementation in ventilators dedicated to Acute, Sub-Acute and Home Care.




PERFORMANCES

ΔP max @24V		90 hPa	fully closed
Q max @24V		320 l/mn	fully opened
Typical w/p @30 l/mn		P = 12.5 (W)	@30 hPa
		P = 22.8 (W)	@60 hPa
LifeTime (L10)		> 40 000 hours*	
Type		Casing integration	

* LifeTime expectancy based on standard operating conditions


 Dynamic transient time*	< 101 ms	@3A max
	< 78 ms	@6A max
	< 68 ms	@10A max
* from 5 to 60 hPa @30 l/mn		
 Noise Level*	< 29 dBa	@10 hPa
	< 40 dBa	@50 hPa
	< 46 dBa	@100 hPa

* with Blower inlet @1m



TECHNICAL DATA

Voltage supply	24 VDC (nom) 28 VDC (max)
Motor type	Brushless with Hall-effect sensors
Dimensions (casing)	130 x 100 x 61 mm (5.3 x 3.9 x 2.4 in)
Weight	0.44 kg (~ 1.00 Lb)
Integration	works in any position/orientation
Temperature	-20 to +50°C ambient
Humidity	0 to 95% RH non condensing
Atmospheric pressure	700 to 1100 hPa
Oxygen compatibility	no




COMPRESSOR MAP


Static ΔP vs Airflow at Constant PWM and Motor Voltage

PWM = Pulse Width Modulation

MFA0300 Turbine



CUSTOMIZATION



Outlet port

- Outlet port male or female connector (22 \varnothing ISO5356-1) or additional auxiliary ports



- Low Leakage sealing as per ISO80601



- O-ring for air inlet



- Custom label



ASK FOR YOUR CUSTOMIZATION

