




























# AIRFAN MICRO BLOWERS PORTFOLIO 2024

All specification are typical values achieved with AIRFAN motor controller MFA0900 and nominal Motor Ke. Refer to the technical specification

Blower reference		O <sub>2</sub> before the turbine (blended O <sub>2</sub> )	Motor cooling (lifetime)	ΔP max (hPa) @24V (zero flow)	Q max (Lpm) @24V (free air)	ΔP max (hPa) @max speed (zero flow)	Q max (Lpm) @max speed (free air)	Data sheet
<b>With Sound proofing housing</b>  <b>The BlueBox</b>  	<u>MFA0500</u>			110	380	119 (25V)	400 (25V)	
	<u>MFA0296</u>			70	320	86 (25V)	340 (25V)	
	<u>MFA0300</u>	---		90	320	122 (28V)	360 (28V)	
	<u>MFA0290</u>	---		76	270	97 (28V)	340 (28V)	
	<u>MFA0295</u> <i>New</i>		---	77	290	116 (28V)	350 (28V)	
<b>Portable Housing</b>  	<u>MFA0249</u> <i>New</i>			> 110	> 340	134 (24V)	360 (24V)	
	<u>MFA0248</u> <i>New</i>			70	320	86 (25V)	380 (25V)	
<b>Without Housing</b>      	<u>MFA0208</u>			70	340	86 (28V)	380 (28V)	
	<u>MFA0206</u>		---	79	300	108 (28V)	360 (28V)	
	<u>MFA0205</u>	---		78	280	106 (28V)	350 (28V)	
	<u>MFA0801</u>		---	+95 / -85	700	± 105 (27V)	750 (27V)	
	<u>MFA0800</u>	---		+95 / -85	660	± 105 (27V)	750 (27V)	
	<u>MFA0810</u> <i>New</i>		---	130	700	---	---	available soon