


MFA0500

Blower for Blended or 100% Oxygen

Specific blower architecture with **patented motor cooling system completely independent** from the air inlet flow.

The **MFA0500** guarantees a **fully homogeneous Air-Oxygen blend** with complete patient safety in the case of an increase in temperature.




PERFORMANCES

ΔP max @24V		110 hPa	static pressure	 Dynamic transient time*	< 113 ms	@3A max
Q max @24V		380 l/mn	freeflow		< 85 ms	@6A max
Typical w/p @30 l/mn		P = 12.5 (W) @30 hPa			< 68 ms	@10A max
		P = 22.1 (W) @60 hPa		* from 5 to 60 hPa @30 l/mn		
LifeTime (L10)		> 40 000 hours*		 Noise Level*	< 29 dBa	@10 hPa
Type		Casing integration			< 40 dBa	@50 hPa
					< 46 dBa	@100 hPa


* LifeTime expectancy based on standard operating conditions

* with Blower inlet @1m




TECHNICAL DATA


Voltage supply	24 VDC (nom) 28 VDC (max)
Motor type	Brushless with Hall-effect sensors
Dimensions (casing)	130 x 100 x 61 mm (5.3 x 3.9 x 2.4 in)
Weight	0.45 kg (~ 1.00 Lb)
Integration	works in any position/orientation
Temperature	+10 to +50°C ambient
Humidity	15 to 95% RH non condensing
Atmospheric pressure	660 to 1060 hPa
Oxygen compatibility	100% O2 compatible



COMPRESSOR MAP



CUSTOMISATION



Outlet port

- ☒ Outlet port male or female connector (22Ø ISO5356-1) or additional auxiliary ports



- ☒ Low Leakage sealing as per ISO80601



- ☒ O-ring for air inlet



- ☒ Custom label



- ☒ Inlet filter for motor cooling



- ☒ Wire Length 150 or custom



CUSTOMISE TO YOUR SPECIFICATIONS



All values listed are typical values with tolerance classification grade 4 according to standard ISO 13448